



Component - Plastics E20811A

DOW CHEMICAL PACIFIC LTD  
40-50 TSING YI RD, TSING YI ISLAND NT HC  
CALIBRE 300V(x), CALIBRE 301V(x)  
Polycarbonate (PC), "CALIBRE", furnished as pellets

Color	Mis Thk (mm)	Flame Class	SWT	HAR	Elec	HTI	HTI	HTI
ALL	1.5	V-2	2	4	125	115	125	125
	3.0	V-2	1	1	125	115	125	125

Comparative Tracking Index (CTI): 2  
High-Voltage Arc Tracking Rate (HVTR): 2  
Dielectric Strength (kV/mm): 12  
(x) - Followed by suffix numbers 3-15 incl. indicating melt flow rate.

Dimensional Stability (%): 0.0  
High Volt. Low Current Arc Resist. (D488) 8  
Volume Resistivity (15° ohm-cm): 15

Dimens.	Tolleranze
$L \leq 4$	$\pm 0.10$
$4 < L \leq 15$	$\pm 0.20$
$15 < L \leq 50$	$\pm 0.30$
$50 < L \leq 100$	$\pm 0.40$

Codice  
**6FCG17A**



Materiale

PC UL94 V2

Colore

BLACK

Descrizione

HORIZONTAL CARD GUIDE

	Scala	Foglio 1	Unità di misura mm
Rev. N	Data 13/04/2017	Disegnato	Controllato