



NOTES:

1. Material : Nylon 66 UL94 V2;
2. Color: Grey;
3. RoHS Compliant;
4. Inside Width: 25.4 mm
5. Cable Max Thickness: 5.00 mm
6. Compatible Thread Sizes: Screw #6 o M3
7. Adhesive: FMS 319  
Double side adhesive temperature -20° to 50°



VIA C. COLLODI, 4/I  
40012 CALDERARA DI RENO (BO) - ITALY  
TEL. (+39) 051 6465211 - FAX (+39) 051 6465251  
sales@fittings.it - www.fittings.it

						DATE	15/07/2019	Dimension		Tolerance	
						SCALE	FIT	L ≤ 4	±0.10		
TITLE	FCM	MOLD-NO.	/	DRAW	ZHR <th>UNIT</th> <td>MM</td> <th>4 &lt; L ≤ 15</th> <td>±0.20</td> <th colspan="2"></th>	UNIT	MM	4 < L ≤ 15	±0.20		
PART NO.	6FFCM26AMA	MAT.	SEE NOTES	DESIGN	ZHR	REV.	A0	15 < L ≤ 50	±0.30		
DWG NO.	/	COLOR	SEE NOTES	APPR.	FDL	VIEW		50 < L ≤ 100	±0.40		